



HEAT PUMPS & DEHUMIDIFIERS

The Causeway Maldon Essex CM9 5PU England  
Tel: +44 (0)1621 856611 Fax: +44 (0)1621 850871  
Net: <http://www.calorex.com> E-mail: [sales@calorex.com](mailto:sales@calorex.com)



## Standard equipment and technical data

Technical data	DH10S
Working range	6 °C to 32 °C
Dehumidification performance/24h	23 litres*
Air flow rate	190 m <sup>3</sup> /h
Voltage / frequency	230 V / 50 Hz
Power consumption	0.62 kW
Water tank	5 litres
L x B x H	315 x 390 x 620 mm
Weight	21 kg

\* 30 °C / 80% r.H. ; Higher dehumidification performances than those described here can be achieved depending on ambient conditions.



### Standard equipment:

- Adjustable hygrostat for constant monitoring of the relative air humidity. If the level set is exceeded the unit automatically switches on. As soon as the required humidity value is reached the compressor switches itself off.
- Warning light to indicate a full catchment tank.
- Overload protection for automatic switch off if the maximum catchment tank volume has been reached.
- Twin condensed water removal system with the option connecting an outflow hose for continuous drying in unmonitored rooms.
- Easily accessible anti-bacterial air filter – simple to clean. Filters animal hairs, fluff, lint and dust, and prevents bacteria growth.